




1/2" ClearFill®Line Plenum-Rated Air-Dielectric Coaxial Cable for In-Building Applications

ClearFill®Line 1/2" low loss air dielectric cable, Plenum-rated, CMP

FEATURES / BENEFITS

- ➔ **Supports Multiple RF Signals**
- ➔ **Complete Shielding**
The solid outer conductor of the ClearFill®Line coaxial cable creates a continuous RF/EMI shield that minimizes system interference.
- ➔ **Outstanding Intermodulation Performance**
RFS coaxial cable's solid inner and outer conductors virtually eliminate intermods. Intermodulation performance is also confirmed with state-of-the-art equipment at the RFS factory.
- ➔ **Wide Range of Applications**
Typical areas of application are: feedlines for plenum-space installations within occupied buildings or structures.



1/2" Plenum-Rated In-Building Cable

Technical Features

APPLICATIONS

Applications	Plenum In-Building
--------------	--------------------

STRUCTURE

Cable Type		Air-Dielectric, Corrugated
Size		1/2"
Inner Conductor	mm (in)	4.8 (0.19) Copper-Clad Aluminum Wire
Dielectric	mm (in)	11.8 (0.464) Extruded Polyethylene
Outer Conductor	mm (in)	13.8 (0.54) Corrugated Copper
Jacket	mm (in)	15.93 (0.627) Plenum Rated / color white

ELECTRICAL SPECIFICATIONS

Impedance	Ω	50 +/- 1
Maximum Frequency	GHz	6
Velocity	%	91
Capacitance	pF/m (pF/ft)	76 (23.2)
Inductance	μH/m (μH/ft)	0.19 (0.058)
Peak Power Rating	kW	40
RF Peak Voltage	Volts	2000
Jacket Spark	Volt RMS	8000
Inner Conductor dc Resistance	Ω/1000 m (Ω/1000 ft)	1.48 (0.45)
Outer Conductor dc Resistance	Ω/1000 m (Ω/1000 ft)	1.9 (0.58)
Return Loss (VSWR) Performance		24.3 (1.13) @ 698-960 MHz 24.3 (1.13) @ 1700-2155 MHz 18 (1.29) @ 4300-5990 MHz
Maximum Return Loss	dB (VSWR)	19 (1.25) in other specified bands
Temperature & Power		High Power Rating

MECHANICAL SPECIFICATIONS

Cable Weight	kg/m (lb/ft)	0.37 (0.25)
Minimum Bending Radius, Single Bend	mm (in)	125 (5)
Minimum Bending Radius, Repeated Bends	mm (in)	254 (10)
Bending Moment	Nm (lb*ft)	4.1 (3)
Tensile Strength	N (lb)	1112 (250)
Recommended / Maximum Clamp Spacing	m (ft)	0.5 / 0.9 (1.8 / 3)



1/2" ClearFill® Line Plenum-Rated Air-Dielectric Coaxial Cable for In-Building Applications

ATTENUATION AND POWER RATING

Frequency MHz	Attenuation		Power kW
	dB/100m	dB/100ft	
0.5	0.15	0.045	40.00
1	0.21	0.064	34.30
1.5	0.26	0.079	27.90
2	0.30	0.091	24.20
10	0.67	0.204	10.70
20	0.95	0.291	7.55
30	1.17	0.358	6.15
50	1.52	0.465	4.74
88	2.04	0.622	3.53
100	2.18	0.665	3.30
108	2.27	0.692	3.17
150	2.70	0.822	2.67
174	2.92	0.889	2.47
200	3.14	0.957	2.30
300	3.89	1.19	1.85
400	4.54	1.39	1.59
450	4.84	1.48	1.49
500	5.13	1.56	1.41
512	5.19	1.58	1.39
600	5.66	1.73	1.28
700	6.16	1.88	1.17
750	6.40	1.95	1.13
800	6.64	2.02	1.09
824	6.75	2.06	1.07
894	7.06	2.15	1.02
900	7.08	2.16	1.02
925	7.19	2.19	1.01
960	7.34	2.24	0.986
1000	7.51	2.29	0.964
1250	8.52	2.60	0.851
1400	9.08	2.77	0.799
1500	9.45	2.88	0.768
1700	10.20	3.09	0.713
1800	10.50	3.20	0.693
2000	11.20	3.40	0.65
2100	11.50	3.50	0.633
2200	11.80	3.59	0.618
2300	12.10	3.69	0.603
2400	12.40	3.78	0.588
2500	12.70	3.87	0.575
2600	13.00	3.96	0.562
2700	13.30	4.05	0.549
3000	14.10	4.31	0.519
3500	15.50	4.73	0.474
3600	15.80	4.81	0.465
4000	16.80	5.13	0.438
4500	18.10	5.51	0.408
5000	19.30	5.88	0.383
5500	20.40	6.23	0.364
6000	21.60	6.58	0.344

Attenuation at 20°C (68°F) cable temperature;
tolerance +/- 5% max.; Mean power rating at
40°C (104°F) ambient temperature

TESTING AND ENVIRONMENTAL

Fire Performance	Flame Retardant, Plenum Rated
Flame Retardant Jacket Specifications	Meets/Exceeds Steiner Tunnel Test Method UL 910, NEC 820-53 (a) CMP, NFPA-262.
Regulatory Compliance	NEC Article 800 Communication Circuits ETL Listed to UL444 Canadian CSA C.22.2/FT6
Installation Temperature	-20 to 60 (-4 to 140) °C(°F)
Storage Temperature	-40 to 85 (-40 to 185) °C(°F)
Operation Temperature	-40 to 85 (-40 to 185) °C(°F)

External Document Links

Notes